



CC_003.2-4

			AFR080	AFR100	AFR150
CAPACIDADE Capacity / Capacidad / Capacité	* FARINHA (kg)-(lb) * Flour / Harina / Farine	MIN - MAX	4 (8,82) 80 (176,37)	5 (11,02) 100 (220,46)	7,5 (16,5) 150 (330,69)
	* MASSA (kg)-(lb) * Dough / Masa / Pâte	MIN - MAX	6,5 (14,33) 130 (280,60)	8 (17,64) 160 (352,74)	12 (26,46) 240 (529,10)
	(l)		230	250	355
POTÊNCIA MOTOR ESPIRAL (kW)-(hp) Power of spiral motor / Potencia motor de la espiral / Puissance du moteur de spirale	CE	400V.3ph.50-60Hz	I 7 (9,5)	II 11 (15)	V -
		400-230V.3ph.50-60Hz	-	-	11 (15)
POTÊNCIA MOTOR TINA (kW)-(hp) Power of bowl motor / Potencia motor de la artesa / Puissance du moteur de la cuve	CE	400V.3ph.50-60Hz	-	-	2,2 (3)
		400-230V.3ph.50-60Hz	-	-	2,2 (3)
Outras voltagens e certificações: sob consulta / Other voltages and certifications: under request / Otros voltajes y certificaciones: bajo consulta / Autres voltages et certifications: sur demande					
PESO LÍQUIDO (kg)-(lb) Net weight / Peso neto / Poids net			730 (1609,36)	882 (1944,46)	888 (1957,68)
	A		870 (34 1/4)	870 (34 1/4)	980 (38 9/16)
	A1		1040 (41)	1040 (41)	1090 (43)
	A2		485 (19 1/8)	485 (19 1/8)	490 (19 5/16)
	B		1500 (59 1/16)	1500 (59 1/16)	1625 (64)
	B1		1590 (62 5/8)	1590 (62 5/8)	1715 (67 1/2)
	C		1465 (51 1/16)	1465 (51 1/16)	1515 (59 5/8)
	C1		1880 (74)	1880 (74)	2020 (79 1/2)
	D		920 (36 1/4)	920 (36 1/4)	970 (38 3/16)
	E		100 (3 15/16)	100 (3 15/16)	100 (3 15/16)

*Baseado em: 60% de hidratação da massa, 12% humidade da farinha, 2°C água / Based on: 60% dough hydration, 12% flour moisture, 2°C water / Basado en: 60% hidratación de la masa, 12% humedad de la harina, 2°C agua / Basé en: 60% hydratation de la pâte, 12% Humidité de la farine, 2°C eau.

V - Velocidade variável / Variable speed / Velocidad variable / Vitesse variable





EQUIPAMENTO DE SÉRIE
Standard-production equipment
Equipamiento de serie
Équipement de série

45-100% HIDRATAÇÃO EXCELENTE OXIGENAÇÃO E INCORPORAÇÃO DE ÁGUA NA MASSA
45-100% hydration: excellent oxygenation and water absorption in the dough / 45-100% hidratación: excelente oxigenación y incorporación de agua en la masa / 45-100% hydratation: excellente oxygénation et incorporation d'eau dans la pâte

STANDARD - ESTRUTURA EM AÇO CARBONO PINTADA
Standard - white painted carbon steel frame / Standard - estructura en acero carbono pintada en blanco / Standard - bâti en acier au carbone

PÉS EM AÇO INOXIDÁVEL AISI 304 E RODAS
Feet in AISI 304 stainless steel and castors / Pies en acero inoxidable AISI 304 y ruedas / Pieds en acier inoxydable AISI 304 et roulettes

MULTISPEED

TINA COM CONE CENTRAL
Bowl with central poste / Artesa con cilindro central / Cuve avec cône central

PERMITE AMASSAR 5% DA CAPACIDADE TOTAL DA TINA
Allows 5% of the total bowl capacity to be kneaded / Permite amasar 5% de la capacidad total de la artesa / Permet de pétrir 5% de la capacité totale du pétrin

DRENO
Drain cap / Desagüe / Bouchon

COMANDO DIGITAL
Digital control / Mandos digitales / Commande digitale

TTP - PROTEÇÃO DA TINA EM POLÍMERO TÉCNICO
Technical polymer bowl's safety cover / Protección para artesa en polímero técnico / Protection de la cuve en polymère technique

GANCHO EM ESPIRAL EM AÇO INOXIDÁVEL
Spiral hook in stainless steel / Gancho en espiral en acero inoxidable / Crochet à spirale en acier inoxydable

CE

INOX - ESTRUTURA EM AÇO INOXIDÁVEL AISI 304
Inox - stainless steel AISI 304 frame / Inox - estructura en acero inoxidable AISI 304 / Inox - bâti en acier inoxydable AISI 304

GTP - PROTEÇÃO DA TINA EM GRELHA
Stainless steel bowl's security bars / Rejilla de protección para artesa / Protection de la cuve en grille

PA1 - PÁ
Paddle / Pala / Palette

RP1 - RASPADOR
Scraper / Rascador / Racleur

ANL - COMANDO ANALÓGICO (SEM MULTISPEED)
Analog control (without multispeed) / Mandos analógicos (sin multispeed) / Commande électromécanique (sans multispeed)

OPÇÕES
Options / Opciones /
Options

IOT - COMANDO IOT COM MULTISPEED
IoT touchscreen with multispeed / Pantalla IoT con multispeed / Commande IoT avec multispeed

TEM - LEITOR DE TEMPERATURA INFRAVERMELHOS
Infrared temperature reader / Lector de temperatura infrarojos / Capteur de température infrarouge

CQI - CAIXA DO QUADRO ELÉTRICO EM AÇO INOXIDÁVEL
Electrical board box in stainless steel / Caja del cuadro eléctrico en acero inoxidable / Boîtier de l'armoire électrique en acier inoxydable

IT1 - INVERSÃO DE TINA
Bowl reverse / Inversor de artesa / Marche arrière

UL-NSF

NR12

DAF001 - DOSEADOR DE ÁGUA (EXTERIOR)
Water meter (external) / Cuentalitros (exterior) / Doseur d'eau (extérieur)

ACESSÓRIOS
Accessories / Accesorios /
Accueil

DAF002 - DOSEADOR DE ÁGUA INTEGRADO
Integrated water meter / Cuentalitros integrado / Doseur d'eau intégré

TUB001 - TUBAGEM PARA APLICAÇÃO DE DOSEADOR DE ÁGUA (DAF001)
Piping installation for water meter (DAF001) / Tubería para cuentalitros externo (DAF001) / Tuyauterie pour doseur d'eau (DAF001)